

# BL330-BR

## Intel® Q35 microATX Board

### PROCESSOR

- LGA 775 socket for:
  - Intel® Core™2 Quad / Intel® Core™2 Duo
  - Intel® Wolfdale 45nm processors
- Supports Intel Enhanced Memory 64 Technology (EMT64T)
- Supports Enhanced Intel SpeedStep Technology (EIST)
- 1333\*/1066/800MHz FSB
- \*Available on CPUs that support 1333MHz FSB

### CHIPSET

- Intel® chipset
  - Intel® Q35 Express chipset
  - Intel® ICH9R I/O Controller Hub

### SYSTEM MEMORY

- Four 240-pin DDR2 DIMM sockets
- Supports dual channel (128-bit wide) memory interface
- Supports 667MHz and 800MHz DDR2 SDRAM
- Supports maximum of 8GB system memory using 512Mbit or 1Gbit technology for x8 and x16 devices
- \*ECC DDR2 DIMMs are not supported

### EXPANSION SLOTS

- 1 PCI Express x16 slot
- 1 PCI Express x4 slot
- 2 PCI slots

### ONBOARD GRAPHICS FEATURES

- Integrated Intel GMA3100
  - Up to 384MB maximum video memory
  - 2048x1536 at 75 Hz maximum resolution

### ONBOARD AUDIO FEATURES

- Realtek ALC662 High Definition audio CODEC
- Six channel DAC supports 16/20/24-bit PCM format for 5.1 channel audio solution
- All DAC support independent 44.1k/48k/96kHz sample rate
- All ADC support independent 44.1k/48k/96kHz sample rate
- Supports 44.1k/48k/96kHz S/PDIF output

### ONBOARD LAN FEATURES

- One Realtek RTL8111B PCI Express Gigabit controller
- Supports 10Mbps, 100Mbps and 1Gbps data transmission
- IEEE 802.3 (10/100Mbps) and IEEE 802.3ab (1Gbps) compliant

### SERIAL ATA INTERFACE

- Supports 6 SATA (Serial ATA) interfaces which are compliant with SATA 1.0 specification
- SATA speed up to 3Gb/s
- RAID 0, RAID 1, RAID 0+1 and RAID 5 (SATA ports 1/2/3/4 only)

### IDE INTERFACE

- JMicron JMB368 PCI Express to PATA host controller
- Supports up to 2 UltraDMA 33/66/100Mbps IDE devices

### REAR PANEL I/O PORTS

- 1 mini-DIN-6 PS/2 mouse port
- 1 mini-DIN-6 PS/2 keyboard port
- 1 DB-25 parallel port
- 1 DB-9 serial port
- 1 DB-15 VGA port
- 1 RJ45 LAN port
- 4 USB 2.0/1.1 ports
- 3 audio jacks for line-in, line-out and mic-in

### I/O CONNECTORS

- 2 connectors for 4 additional external USB 2.0/1.1 ports
- 1 connector for external serial port
- 1 DIO connector
- 1 front audio connector for line-out and mic-in jacks
- 1 CD-in internal audio connector
- 1 S/PDIF-out connector
- 1 connector for IrDA interface
- 6 Serial ATA connectors
- 1 40-pin IDE connector
- 1 floppy connector
- 1 24-pin ATX power connector
- 1 4-pin 12V power connector
- 1 chassis open connector
- 1 front panel connector
- 3 fan connectors

### BIOS

- Award BIOS
- 8Mbit flash memory

### ENERGY EFFICIENT DESIGN

- Supports ACPI specification and OS Directed Power Management
- Supports ACPI STR (Suspend to RAM) function
- Wake-On-Events include:
  - Wake-On-PS/2 Keyboard/Mouse
  - Wake-On-USB Keyboard/Mouse
  - Wake-On-LAN and Wake-On-Ring
  - RTC timer to power-on the system
- System power management supported
- Microsoft®/Intel® APM 1.2 compliant
- Soft Power supported - ACPI v1.0a specification
- AC power failure recovery

### DAMAGE FREE INTELLIGENCE

- Monitors CPU/system/AUX temperature and overheat alarm
- Monitors CPU(V)/5V/1.5V/dimm(V)/12V/VBAT(V)/3.3V/V3.3sb(V) voltages and failure alarm
- Monitors CPU/system/2nd fan speed and failure alarm
- Read back capability that displays temperature, voltage and fan speed
- Watchdog timer function

### TEMPERATURE

- 0°C to 60°C

### HUMIDITY

- 10% to 90%

### PCB

- 4 layers, microATX form factor
- 24.4cm (9.6") x 24.4cm (9.6")

### SAFETY

- UL, cUL, FCC Class B, CE

### REAR PANEL I/O PORTS

