

CT950-B

Intel® 945GME 3.5" Board

PROCESSOR

Active Cooler Included with Board.

Intel® Core™ 2 Duo mobile processor

- Intel® Core™ Duo/Solo processor
 - 667MHz/533MHz system data bus
- Intel® Celeron® M processor
 - 533MHz system data bus
- Processor socket: mPGA478M

Note: Ultra Low Voltage (ULV) and Low Voltage (LV) processor is available on special order.

CHIPSET

- Intel® chipset
 - Intel® 945GME Express chipset
 - Intel® 82801GBM I/O Controller Hub (ICH7M)

SYSTEM MEMORY

- One 200-pin SODIMM socket
- Supports 400MHz, 533MHz and 667MHz DDR2 SDRAM
- Supports maximum of 2GB system memory using 256Mbit, 512Mbit or 1Gbit technology for x8 and x16 devices

ONBOARD GRAPHICS FEATURES

- Integrated graphics interface
 - Analog CRT
 - Integrated 400MHz RAMDAC
 - Analog monitor supports up to UXGA
 - LVDS interface
 - Panel support up to UXGA (1600x1200)
 - 25MHz-112MHz single/dual channel @ 24bpp, TFT panel type support
- Internal graphics features
 - DVMT 3.0 support
 - Intel® Dual-Frequency Graphics Technology
 - Intel® Smart 2D Display Technology
 - Dual Independent display pipes
 - Intel Gen 3.5 Integrated Graphics Engine

ONBOARD AUDIO FEATURES

- Realtek ALC655
- 16-bit stereo full-duplex codec with independent variable sampling rate
- 2-channel audio output

ONBOARD LAN FEATURES

- One Realtek RTL8111C PCI Express Gigabit controller
- Supports 10Mbps, 100Mbps and 1Gbps data transmission
- IEEE 802.3 (10/100Mbps) and IEEE 802.3ab (1Gbps) compliant

SERIAL ATA INTERFACE

- Supports one Serial ATA interface which is compliant with SATA 1.0 specification (1.5Gbps interface)

IDE INTERFACE

- One 44-pin IDE connector supports up to two IDE devices
- Supports Ultra ATA 100/66/33 (this will depend on the IDE cable used)

I/O PORTS

- 1 DB-15 VGA port
- 1 RJ45 LAN port
- 1 DC-in 12V jack
- 1 port for PS/2 keyboard and PS/2 mouse ports
- 1 DB-9 serial port
- 1 Serial ATA port

I/O CONNECTORS

- 1 CompactFlash socket
- 1 connector for 2 additional external USB 2.0/1.1 ports
- 1 connector for 1 external RS232/RS485/RS422 serial port
- 1 LVDS LCD panel connector
- 1 LCD/inverter power connector
- 1 audio connector for 2 mic-in and 1 line-out
- 1 44-pin IDE connector
- 1 front panel connector
- 2 fan connectors

BIOS

- Award BIOS
- 4Mbit flash memory

ENERGY EFFICIENT DESIGN

- Supports ACPI specification and OS Directed Power Management
- Wake-On-Events include:
 - Wake-On-PS/2 Keyboard/Mouse
 - Wake-On-USB Keyboard/Mouse
 - Wake-On-LAN and Wake-On-Ring
 - RTC timer to power-on the system
- System power management supported
- CPU stopped clock control
- Microsoft®/Intel® APM 1.2 compliant
- Soft Power supported - ACPI v1.0a specification
- AC power failure recovery

DAMAGE FREE INTELLIGENCE

- Monitors CPU/system temperature and overheat alarm
- Monitors CPU/system fan speed and failure alarm
- Read back capability that displays temperature, voltage and fan speed
- Watchdog timer function

EXPANSION SLOT

- 1 mini PCI slot

TEMPERATURE

- 0°C to 60°C

HUMIDITY

- 10% to 90%

PCB

- 10.2cm (4.02") x 14.65cm (5.76")

REAR PANEL I/O PORTS

